

Package: golden (via r-universe)

September 16, 2026

Type Package

Title Framework for Patient-Level Microsimulation of Risk Factor
Trajectories & Hazard-Based Events

Version 0.0.4

Date 2026-08-24

Description Fast, flexible, patient-level microsimulation.
Time-stepped simulation with a 'C++' back-end from
user-supplied initial population, trajectories, hazards, and
corresponding event transitions. User-defined aggregate time
series histories are returned together with the final
population. Designed for simulation of chronic diseases with
continuous and evolving risk factors, but could easily be
applied more generally.

License MIT + file LICENSE

Imports Rcpp (>= 1.1.0), data.table

LinkingTo Rcpp

Suggests testthat (>= 3.0.0), SciViews, knitr, rmarkdown, ggplot2

Config/testthat/edition 3

Depends R (>= 3.5)

LazyData true

RoxygenNote 7.3.3

Encoding UTF-8

VignetteBuilder knitr

NeedsCompilation yes

Author Pete Dodd [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5825-9347>>), Robert Chisholm [aut]
(ORCID: <<https://orcid.org/0000-0002-6983-2759>>), University of
Sheffield [cph], Horizon Europe [fnd]

Maintainer Pete Dodd <p.j.dodd@sheffield.ac.uk>

Repository <https://petedodd.r-universe.dev>

Date/Publication 2026-08-24 13:00:02 UTC
RemoteUrl <https://github.com/cran/golden>
RemoteRef HEAD
RemoteSha 1eb2bc345ee8cf206f910d7a3235c514972c2ba1

Contents

bmi_fits	2
check_column	3
check_hazard	4
check_history	5
check_parameters	6
check_trajectory	7
check_transition	8
create_cohort	8
globorisk_coefs	9
globorisk_cvdr	10
globorisk_rf	11
golden	12
lifetable_data	12
new_column	13
new_hazard	14
new_history	15
new_parameters	15
new_trajectory	17
new_transition	18
pop_snapshot	18
print.golden_hazard	19
print.golden_history	20
print.golden_history_column	21
print.golden_parameters	21
print.golden_timing	22
print.golden_trajectory	24
print.golden_transition	25
run_simulation	25
Index	27

Description

This dataset contains example fits of body mass index (BMI) to gamma distributions for the United States in 2022. The original data were taken from an analysis of the contribution of undernutrition to tuberculosis incidence, which was published in the Lancet Global Health in 2026. The data on which these fits are based is from the NCD Risk Factor Collaboration (NCD-RisC) estimates dataset.

Usage

bmi_fits

Format

- A data.frame/data.table with 28 rows and 4 variables:
- sex** Biological sex ('char'): Men, Women
 - acat** Age category in years ('char'): 0-4, 5-9, ..., 85plus
 - k** Gamma distribution shape parameter ('num'): $k > 0$
 - theta** Gamma distribution scale parameter ('num'): $\theta > 0$

Source

<https://github.com/petedodd/bmitb>

check_column	<i>Validate an history column object If validation fails, an exception will be raised.</i>
--------------	--

Description

Validate an history column object If validation fails, an exception will be raised.

Usage

check_column(column, initPop = NULL)

Arguments

- column An S3 object of class "golden_history_column"
- initPop (Optional) data.table to check columns required by functions exist

Value

No return value, called for side effects.

Examples

```
library(data.table)
dt <- data.table(a = rep(0, 100))
# Create an S3 golden_history_column
col <- new_column("sum_a", sum, c("a"))
# check_column() will not throw an exception
# as col is a valid S3 golden_history_column
# and dt contains column "a"
check_column(col, dt)
```

check_hazard	<i>Validate an hazard object If validation fails, an exception will be raised.</i>
--------------	--

Description

Validate an hazard object If validation fails, an exception will be raised.

Usage

```
check_hazard(hazard, initPop = NULL)
```

Arguments

hazard	An S3 object of class "golden_hazard"
initPop	(Optional) data.table to check columns required by functions exist

Value

No return value, called for side effects.

Examples

```
library(data.table)
N <- 100
dt <- data.table(a = runif(N, 0, 1), b = rep(0, N))
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
```

```

    )
# check_hazard() will not throw an exception
# as haz is a valid S3 golden_hazard
# and dt contains column "a"
check_hazard(haz, dt)

```

check_history	<i>Validate an history object If validation fails, an exception will be raised.</i>
---------------	---

Description

Validate an history object If validation fails, an exception will be raised.

Usage

```
check_history(history, initPop = NULL)
```

Arguments

history	An S3 object of class "golden_history"
initPop	(Optional) data.table to check columns required by functions exist

Value

No return value, called for side effects.

Examples

```

library(data.table)
dt <- data.table(a = rep(0, 100))
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
# check_history() will not throw an exception
# as hist is a valid S3 golden_history
# and dt contains column "a" used by the column
check_history(hist, dt)

```

check_parameters	<i>Validate the configuration passed to run_simulation() If validation fails, an exception will be raised.</i>
------------------	--

Description

Validate the configuration passed to run_simulation() If validation fails, an exception will be raised.

Usage

```
check_parameters(parameters, initPop = NULL)
```

Arguments

parameters	An golden_parameters S3 object to be validated
initPop	data.frame which contains the columns required by parameters

Value

No return value, called for side effects.

Examples

```
library(data.table)
N <- 100
dt <- data.table(a = runif(N, 0, 1), b = rep(0, N))
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Create an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
# Create an S3 golden_parameters
```

```

params <- new_parameters(
  hazards = haz,
  trajectories = trj,
  steps = 10,
  debug = FALSE,
  history = hist
)
# check_parameters() will not throw an exception
# as params is a valid S3 golden_parameters
# and dt contains columns "a" and "b"
check_parameters(params, dt)

```

check_trajectory	<i>Validate an trajectory object If validation fails, an exception will be raised.</i>
------------------	--

Description

Validate an trajectory object If validation fails, an exception will be raised.

Usage

```
check_trajectory(trajectory, initPop = NULL)
```

Arguments

trajectory	An S3 object of class "golden_trajectory"
initPop	(Optional) data.table to check columns required by functions exist

Value

No return value, called for side effects.

Examples

```

library(data.table)
dt <- data.table(b = rep(0, 100))
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Create an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
# check_trajectory() will not throw an exception
# as trj is a valid S3 golden_trajectory
# and dt contains column "b"
check_trajectory(trj, dt)

```

check_transition	<i>Validate an transition object If validation fails, an exception will be raised.</i>
------------------	--

Description

Validate an transition object If validation fails, an exception will be raised.

Usage

```
check_transition(transition, initPop = NULL)
```

Arguments

transition	An S3 object of class "golden_transition"
initPop	(Optional) data.table to check columns required by functions exist

Value

No return value, called for side effects.

Examples

```
library(data.table)
dt <- data.table(b = rep(0, 100))
# Define a transition function, which sets all columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Define an S3 golden_transition
trn <- new_transition(test_transition, c(), "b")
# check_transition() will not throw an exception
# as trn is a valid S3 golden_transition
# and dt contains column "b"
check_transition(trn, dt)
```

create_cohort	<i>Create a new cohort</i>
---------------	----------------------------

Description

Temporary testing method, probably replaced in future with R's simdata package or similar

Usage

```
create_cohort(demog, N)
```

Arguments

demog	Demographic information containing columns AgeGrp/PopMale/PopFemale/PopTotal
N	Size of the population to generate

Value

A sample population data.table, with columns male/age/bmi/death

Examples

```
library(data.table)
demog <- data.table(
  AgeGrp = c(0, 1, 2, 3),
  PopMale = c(1000, 1100, 1050, 980),
  PopFemale = c(950, 1020, 1005, 970)
)
demog[, PopTotal := PopMale + PopFemale]
cohort <- create_cohort(demog, 100)
```

globoRisk_coefs	<i>Example globoRisk coefficients</i>
-----------------	---------------------------------------

Description

Example data on cardiovascular disease (CVD) risk from the GloboRisk model, which is a model for estimating 10-year risk of fatal and non-fatal CVD events, see:

[https://doi.org/10.1016/S2213-8587\(17\)30015-3](https://doi.org/10.1016/S2213-8587(17)30015-3) [https://doi.org/10.1016/S2213-8587\(15\)00081-9](https://doi.org/10.1016/S2213-8587(15)00081-9)

These data are available in the ‘globoRisk’ R package, see the source link below. This subset is for the United States, and contains the coefficients for the risk prediction equations.

The exact extraction of these data from the ‘globoRisk’ package is in the ‘data-raw/dataprep.R’ file in this package.

Usage

```
globoRisk_coefs
```

Format

A data.frame/data.table with 1 rows and 18 variables:

type Risk model type (‘char’, set to "office").

main_sbpc Coefficient for centered and scaled systolic blood pressure (‘num’).

main_tcc Coefficient for centered and scaled total cholesterol (‘num’).

main_Idm_1 Variable not used in this model, but included as ‘NA’ for completeness (‘num’).

main_smok Variable not used in this model, but included as ‘NA’ for completeness (‘num’).

main_sexdm Variable not used in this model, but included as 'NA' for completeness ('num').

main_sexsmok Variable not used in this model, but included as 'NA' for completeness ('num').

tv_c_sbpc Coefficient for centered and scaled systolic blood pressure by age interaction term ('num').

tv_c_tcc Variable not used in this model, but included as 'NA' for completeness ('num').

tv_c_dm Variable not used in this model, but included as 'NA' for completeness ('num').

tv_c_smok Variable not used in this model, but included as 'NA' for completeness ('num').

main_bmi5c Coefficient for centered and scaled body mass index (BMI) ('num').

main_smokc Coefficient for centered and scaled smoking status ('num').

main_sexsmokc Coefficient for centered and scaled smoking by sex interaction term ('num').

tv_c_smokc Coefficient for centered and scaled smoking status by age interaction term ('num').

tv_c_bmi5c Coefficient for centered and scaled BMI by age interaction term ('num').

main_sbpsex Variable not used in this model, but included as 'NA' for completeness ('num').

lac Globorisk use Local Area Countries flag ('num', set to 0).

Source

<https://github.com/boyerch/globorisk>

globorisk_cvdr

Example globorisk baseline hazard

Description

Example data on cardiovascular disease (CVD) risk from the Globorisk model, which is a model for estimating 10-year risk of fatal and non-fatal CVD events, see:

[https://doi.org/10.1016/S2213-8587\(17\)30015-3](https://doi.org/10.1016/S2213-8587(17)30015-3) [https://doi.org/10.1016/S2213-8587\(15\)00081-9](https://doi.org/10.1016/S2213-8587(15)00081-9)

These data are available in the 'globorisk' R package, see the source link below. This subset is for the United States in 2000, and contains the baseline hazard.

The exact extraction of these data from the 'globorisk' package is in the 'data-raw/dataprep.R' file in this package.

Usage

```
globorisk_cvdr
```

Format

A data.frame/data.table with 20 rows and 4 variables:

agec Age category ('int'): 1,...,10.

sex Sex ('int'): 0, 1.

cvd_0 Baseline hazard per year for CVD events ('num').

agesex Age and sex concatenated category ('char'): "1_0", "1_1", ..., "10_1".

Source

<https://github.com/boyercb/globorisk>

globorisk_rf

Example globorisk reference values

Description

Example data on cardiovascular disease (CVD) risk from the Globorisk model, which is a model for estimating 10-year risk of fatal and non-fatal CVD events, see:

[https://doi.org/10.1016/S2213-8587\(17\)30015-3](https://doi.org/10.1016/S2213-8587(17)30015-3) [https://doi.org/10.1016/S2213-8587\(15\)00081-9](https://doi.org/10.1016/S2213-8587(15)00081-9)

These data are available in the ‘globorisk’ R package, see the source link below. This subset is for the United States, and contains the reference values for centering.

The exact extraction of these data from the ‘globorisk’ package is in the ‘data-raw/dataprep.R’ file in this package.

Usage

globorisk_rf

Format

A data.frame/data.table with 18 rows and 9 variables:

iso ISO country code (‘char’): "USA".

agec Age category (‘int’): 1,...,10.

sex Sex (‘int’): 0, 1.

mean_sbp Systolic blood pressure mean value for centering (‘num’).

mean_tc Total cholesterol mean value for centering (‘num’).

mean_dm Diabetes mean value for centering (‘num’).

mean_smk Smoking status mean value for centering (‘num’).

mean_bmi Body mass index mean value for centering (‘num’).

agesex Age and sex concatenated category (‘char’): "1_0", "1_1", ..., "9_1".

Source

<https://github.com/boyercb/globorisk>

golden	<i>Golden: Framework for Patient-Level Microsimulation of Risk Factor Trajectories & Hazard-Based Events</i>
--------	--

Description

Fast, flexible, patient-level microsimulation. Time-stepped simulation with a 'C++' back-end from user-supplied initial population, trajectories, hazards, and corresponding event transitions. User-defined aggregate time series histories are returned together with the final population. Designed for simulation of chronic diseases with continuous and evolving risk factors, but could easily be applied more generally.

Author(s)

Maintainer: Pete Dodd <p.j.dodd@sheffield.ac.uk> (ORCID)

Authors:

- Robert Chisholm <robert.chisholm@sheffield.ac.uk> (ORCID)

Other contributors:

- University of Sheffield [copyright holder]
- Horizon Europe [funder]

Examples

```
## Not run:  
# A full example can be found in the vignettes  
  
## End(Not run)
```

lifetable_data	<i>Example life table data</i>
----------------	--------------------------------

Description

Example life table data for the United States from 2000 to 2100, with age-specific mortality rates for each sex and in total. The original data were taken from the World Population Prospects 2024 revision, which is published by the United Nations Department of Economic and Social Affairs, Population Division.

<https://population.un.org/wpp/>

The data on which these life tables are based is from the WPP 2024 revision, as made available through the 'wpp2024' R package available from the source below. The exact extraction of these data from the WPP 2024 revision is in the 'data-raw/dataprep.R' file in this package.

Usage

lifetable_data

Format

- A data.frame/data.table with 10,201 rows and 5 variables:
- year** The year of the life table data ('integer'), ranging from 2000 to 2100.
 - age** The age group for the life table data ('integer'), ranging from 0 to 100.
 - mxM** Actuarial mortality for men; age-specific hazard of death ('num').
 - mxF** Actuarial mortality for women; age-specific hazard of death ('num').
 - mxB** Actuarial mortality for both sexes combined; age-specific hazard of death ('num').

Source

<https://github.com/PPgp/wpp2024>

new_column	Create a new golden_history_column
------------	------------------------------------

Description

Create a new golden_history_column

Usage

new_column(name, fn, args, filter_fn = NULL, filter_args = NULL)

Arguments

- name** Name of the column in the output data-table
- fn** Reduction function, which converts the input columns to a single value
- args** Names of columns and special variables to be passed to fn
- filter_fn** (Optional) Filter function, which returns a bool vector denoting which rows should be reduced
- filter_args** (Optional) Names of columns and special variables to be passed to filter_fn. Required if filter_fn is

Value

An object of class "golden_history_column"

Examples

```
# Create an S3 golden_history_column named "sum_a", using sum(). with column "a"
col <- new_column("sum_a", sum, c("a"))
```

new_hazard	<i>Create a new hazard object</i>
------------	-----------------------------------

Description

Create a new hazard object

Usage

```
new_hazard(
  fn,
  args,
  transitions,
  freq = 1,
  first = 1,
  last = 2147483647,
  name = NULL
)
```

Arguments

fn	Function which calculates the hazard likelihood
args	Character vector of parameter names expected by fn
transitions	Transition object(s) to be applied where the hazard is successful
freq	(Optional) The frequency of hazard execution, hazards always execute on first step
first	(Optional) First step the hazard should be enabled (initial step is index 1)
last	(Optional) Last step the hazard should be enabled (initial step is index 1)
name	(Optional) Name used in error messages and similar. Defaults to an automatic name

Value

An object of class "golden_hazard"

Examples

```
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
```

```
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
```

new_history	Create a new golden_history
-------------	-----------------------------

Description

Create a new golden_history

Usage

```
new_history(columns, frequency = 1)
```

Arguments

columns	golden_history_column S3 object(s)
frequency	The number of simulation steps per history collection.

Value

An object of class "golden_history"

Examples

```
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
```

new_parameters	Create a new golden_parameters
----------------	--------------------------------

Description

Create a new golden_parameters

Usage

```
new_parameters(
  hazards = list(),
  trajectories = list(),
  steps,
  random_seed = 0,
  debug = TRUE,
  print_timing = TRUE,
  history = NULL
)
```

Arguments

hazards	golden_hazard S3 object(s)
trajectories	golden_trajectory S3 object(s)
steps	Number of steps to run
random_seed	Seed to be used for random generation. If set 0, current R random state will be used.
debug	(TRUE/FALSE) flag indicating whether validation checks are enabled. These catch NaN, but reduce performance
print_timing	(TRUE/FALSE) flag indicating whether a per-function timing report should be printed after the simulation, this will always be suppressed for fast (≤ 1 second) simulations.
history	golden_history S3 object representing the columns of data to be aggregated during simulation

Value

An object of class "golden_parameters"

Examples

```
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Create an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
# Create an S3 golden_parameters
params <- new_parameters(
  hazards = haz,
  trajectories = trj,
  steps = 10,
  debug = FALSE,
  history = hist
)
```

new_trajectory	Create a new trajectory object
----------------	--------------------------------

Description

Create a new trajectory object

Usage

```
new_trajectory(fn, args, states, name = NULL)
```

Arguments

fn	Function defining the trajectory function
args	Character vector of parameter names expected by fn
states	Name(s) of the column(s) where the result(s) of the trajectory function is to be stored
name	(Optional) Name used in error messages and similar. Defaults to an automatic name

Value

An object of class "golden_trajectory"

Note

If a list is passed to states, fn must return a list of equal length

Examples

```
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Create an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
```

new_transition	Create a new transition object
----------------	--------------------------------

Description

Create a new transition object

Usage

```
new_transition(fn, args, states, name = NULL)
```

Arguments

fn	Function defining the transition functions
args	Character vector of parameter names expected by fn
states	Name(s) of the column(s) where the result of the transition function is to be stored
name	(Optional) Name used in error messages and similar. Defaults to an automatic name

Value

An object of class "golden_transition"

Examples

```
# Define a transition function, which sets all columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Define an S3 golden_transition
trn <- new_transition(test_transition, c(), "b")
```

pop_snapshot	Example population structure
--------------	------------------------------

Description

Example population data for the United States for 2000, with age-specific populations in thousands. The original data were taken from the World Population Prospects 2024 revision, which is published by the United Nations Department of Economic and Social Affairs, Population Division.

<https://population.un.org/wpp/>

The data on which these population data are based is from the WPP 2024 revision, as made available through the ‘wpp2024’ R package available from the source below. The exact extraction of these data from the WPP 2024 revision is in the ‘data-raw/dataprep.R’ file in this package.

Usage

```
pop_snapshot
```

Format

A matrix with 101 rows and 2 columns:

popM Named first matrix column: the male population in thousands for each age group, with rows for ages 0 to 100 years.

popF Named second matrix column: the female population in thousands for each age group, with rows for ages 0 to 100 years.

Source

<https://github.com/PPgp/wpp2024>

```
print.golden_hazard
```

Print the contents of a golden_hazard type S3 object

Description

Print the contents of a golden_hazard type S3 object

Usage

```
## S3 method for class 'golden_hazard'
print(x, ..., indent = 0L)
```

Arguments

x	The object to be printed
...	Not used. Included for S3 method compatibility.
indent	(Optional) The level the printing is indented, useful if nested within another S3 object

Value

No return value, called for side effects.

Examples

```
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
print(haz)
```

`print.golden_history` *Print the contents of a golden_history type S3 object*

Description

Print the contents of a golden_history type S3 object

Usage

```
## S3 method for class 'golden_history'
print(x, ..., indent = 0L)
```

Arguments

<code>x</code>	The object to be printed
<code>...</code>	Not used. Included for S3 method compatibility.
<code>indent</code>	(Optional) The level the printing is indented, useful if nested within another S3 object

Value

No return value, called for side effects.

Examples

```
# Create an S3 golden_history
hist <- new_history(new_column("sum_a", sum, c("a")))
print(hist)
```

```
print.golden_history_column
```

Print the contents of a golden_history_column type S3 object

Description

Print the contents of a golden_history_column type S3 object

Usage

```
## S3 method for class 'golden_history_column'  
print(x, ..., indent = 0L)
```

Arguments

x	The object to be printed
...	Not used. Included for S3 method compatibility.
indent	(Optional) The level the printing is indented, useful if nested within another S3 object

Value

No return value, called for side effects.

Examples

```
# Create an S3 golden_history_column  
col <- new_column("sum_a", sum, c("a"))  
print(col)
```

```
print.golden_parameters
```

Print the contents of a golden_parameters type S3 object

Description

Print the contents of a golden_parameters type S3 object

Usage

```
## S3 method for class 'golden_parameters'  
print(x, ..., indent = 0)
```

Arguments

<code>x</code>	The object to be printed
<code>...</code>	Not used. Included for S3 method compatibility.
<code>indent</code>	(Optional) The level the printing is indented, useful if nested within another S3 object

Value

No return value, called for side effects.

Examples

```
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Create an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
# Create an S3 golden_parameters
params <- new_parameters(
  hazards = haz,
  trajectories = trj,
  steps = 10,
  debug = FALSE,
  history = hist
)
print(params)
```

Description

Print the contents of a golden_timing type S3 object

Usage

```
## S3 method for class 'golden_timing'
print(x, ...)
```

Arguments

x	The object to be printed
...	Not used. Included for S3 method compatibility.

Value

No return value, called for side effects.

Examples

```
library(data.table)
N <- 100
dt <- data.table(a = runif(N, 0, 1), b = rep(0, N))
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Define an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
# Define an S3 golden_parameters
params <- new_parameters(
  hazards = haz,
  trajectories = trj,
  steps = 10,
  debug = FALSE,
  history = hist
```

```
)  
# Run the simulation to collect results  
results <- run_simulation(dt, params)  
print(results$timing)
```

```
print.golden_trajectory
```

Print the contents of a golden_trajectory type S3 object

Description

Print the contents of a golden_trajectory type S3 object

Usage

```
## S3 method for class 'golden_trajectory'  
print(x, ..., indent = 0L)
```

Arguments

x	The object to be printed
...	Not used. Included for S3 method compatibility.
indent	(Optional) The level the printing is indented, useful if nested within another S3 object

Value

No return value, called for side effects.

Examples

```
# Define a trajectory function, which adds 2 to all members of the input vector  
test_trajectory <- function(a) {  
  return (a + 2)  
}  
# Create an S3 golden_trajectory  
trj <- new_trajectory(test_trajectory, c("b"), "b")  
print(trj)
```

```
print.golden_transition
```

Print the contents of a golden_transition type S3 object

Description

Print the contents of a golden_transition type S3 object

Usage

```
## S3 method for class 'golden_transition'
print(x, ..., indent = 0L)
```

Arguments

x	The object to be printed
...	Not used. Included for S3 method compatibility.
indent	(Optional) The level the printing is indented, useful if nested within another S3 object

Value

No return value, called for side effects.

Examples

```
# Define a transition function, which sets all columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Define an S3 golden_transition
trn <- new_transition(test_transition, c(), "b")
print(trn)
```

```
run_simulation
```

Execute a patient trajectory simulation

Description

Execute a patient trajectory simulation

Usage

```
run_simulation(initPop, parameters)
```

Arguments

initPop	data.table containing initial population for simulation
parameters	Simulation configuration

Value

An list containing final population, history and timing data.tables

Examples

```
library(data.table)
N <- 100
dt <- data.table(a = runif(N, 0, 1), b = rep(0, N))
# Define a hazard function, which returns a vector of equal length uncertainties
test_hazard <- function(a) {
  ret <- (a < 0.5)
}
# Define a transition function, which sets all "b" columns affected by the hazard to 100
test_transition <- function() {
  return (100)
}
# Create an S3 golden_hazard
haz <- new_hazard(
  test_hazard,
  c("a"),
  new_transition(test_transition, c(), "b")
)
# Define a trajectory function, which adds 2 to all members of the input vector
test_trajectory <- function(a) {
  return (a + 2)
}
# Define an S3 golden_trajectory
trj <- new_trajectory(test_trajectory, c("b"), "b")
# Create an S3 golden_history, containing 1 golden_history_column
hist <- new_history(new_column("sum_a", sum, c("a")))
# Define an S3 golden_parameters
params <- new_parameters(
  hazards = haz,
  trajectories = trj,
  steps = 10,
  debug = FALSE,
  history = hist
)
# Run the simulation to collect results
results <- run_simulation(dt, params)
```

Index

* datasets

- bmi_fits, [2](#)
- globorisk_coefs, [9](#)
- globorisk_cvdr, [10](#)
- globorisk_rf, [11](#)
- lifetable_data, [12](#)
- pop_snapshot, [18](#)

bmi_fits, [2](#)

check_column, [3](#)
check_hazard, [4](#)
check_history, [5](#)
check_parameters, [6](#)
check_trajectory, [7](#)
check_transition, [8](#)
create_cohort, [8](#)

globorisk_coefs, [9](#)
globorisk_cvdr, [10](#)
globorisk_rf, [11](#)
golden, [12](#)
golden-package (golden), [12](#)

lifetable_data, [12](#)

new_column, [13](#)
new_hazard, [14](#)
new_history, [15](#)
new_parameters, [15](#)
new_trajectory, [17](#)
new_transition, [18](#)

pop_snapshot, [18](#)
print.golden_hazard, [19](#)
print.golden_history, [20](#)
print.golden_history_column, [21](#)
print.golden_parameters, [21](#)
print.golden_timing, [22](#)
print.golden_trajectory, [24](#)
print.golden_transition, [25](#)

run_simulation, [25](#)